



Shock Indicator - Shipping Damage Monitoring

Product Overview

Shock Indicator 2 impact indicators are single-use devices that deter mishandling and reduce damage related costs by indicating when products have been exposed to a potentially damaging impact during transit or in storage.

These labels are tamperproof, mechanically activated devices that turn bright red when an impact occurs.



Selection Guide

There are two things you need to know to begin selecting an impact indicator sensitivity: shipment size and weight. The selection guide should always be used as a starting point only. The label that will be best suited to your application will also take into account product fragility and packaging.

	5 - 15 ft³ .14 - .42 m³	15 - 50 ft³ .42 - 1.42 m³	50 - 100 ft³ 1.42 - 2.83 m³	100 - 250 ft³ 2.83 - 7.08 m³	250 - 500 ft³ 7.08 - 14.16 m³	500 - 1,000 ft³ 14.16 - 304.8 m³	1,000+ ft³ 304.8+ m³
0 - 10 lbs 0 - 5 kg	75G	75G	50G	37G	N/A	N/A	N/A
10 - 25 lbs 5 - 11 kg	75G	50G	50G	37G	25G	N/A	N/A
25 - 50 lbs 11 - 23 kg	50G	50G	37G	25G	25G	15G	N/A
50 - 100 lbs 23 - 45 kg	50G	37G	37G	25G	15G	15G	10G
100 - 250 lbs 45 - 113 kg	37G	37G	25G	25G	15G	15G	10G
250 - 1,000 lbs 113 - 454 kg	37G	25G	25G	15G	15G	10G	10G
1,000 - 2,000 lbs 454 - 907 kg	25G	25G	25G	15G	15G	10G	5G
2,000 - 5,000 lbs 907 - 2,268 kg	25G	25G	15G	15G	10G	10G	5G
5,000 - 10,000 lbs 2,268 - 4,536 kg	25G	15G	15G	15G	10G	10G	5G
10,000 - 15,000 lbs 4,536 - 6,804 kg	N/A	15G	15G	10G	10G	5G	5G
15,000 - 20,000 lbs 6,804 - 9,072 kg	N/A	N/A	10G	10G	5G	5G	5G
20,000 - 30,000 lbs 9,072 - 13,608 kg	N/A	N/A	N/A	5G	5G	5G	5G
30,000+ lbs 13,608+ kg	N/A	N/A	N/A	N/A	5G	5G	5G

Specifications

Model	Shock indicator
Dimensions	42.93 x 42.93 x 6.35 mm
Sensitivity Range	5G, 10G, 15G, 25G, 37G, 50G, 75G, 100G
Impact Duration	0.5 - 50 ms
Tolerance	±15%
Adhesive	Acrylic adhesive
Materials	Cardboard, ABS, backing adhesive
Operating Temperature	-25°C to 80°C (-13°F to 176°F)
Shelf life	2 years when stored at standard temperature and pressure(20°C,1ATM)